STEAM PRESSURE REDUCING VALVE MODEL COSR-21

SELF-ACTUATED PRESSURE REDUCING VALVE WITH SHOCK-ABSORBING PISTON

Features

TLV

Technologically advanced pressure reducing valve for accurate control in process steam systems.

- 1. Self-aligning shock-absorbing spherical piston and advanced pilot regulator designs maintain secondary steam pressure accuracy, even during adverse process conditions.
- 2. Major internal components made of stainless steel for long service life.
- 3. Large surface area integral screen for pilot valve extend trouble-free service.
- 4. Internal secondary pressure-sensing channel makes external sensing line unnecessary.
- 5. COSR-21, sizes 65 mm and larger have a silencer for noise reduction.



Specifications

Model	COSR-21
Connection	Flanged
Size (mm)	15, 20, 25, 32, 40, 50, 65, 80, 100
Body Material	Ductile Cast Iron
Maximum Operating Pressure (MPaG) PMO	2.1
Maximum Operating Temperature (°C) TMO	220
Primary Pressure Range (MPaG)	1.35 to 2.1
Adjustable Pressure Range	Within 10 to 84% of primary pressure but with a minimum pressure of 0.55 MPaG
(all conditions must be met)	Maximum differential pressure 0.85 MPa
Minimum Adjustable Flow Rate	5% of rated flow rate (For 65 mm to 100 mm: 10% of rated flow rate)

PRESSURE SHELL DESIGN CONDITIONS (NOT OPERATING CONDITIONS): Maximum Allowable Pressure (MPaG) PMA: 2.1

Maximum Allowable Temperature (°C) TMA: 220



To avoid abnormal operation, accidents or serious injury, DO NOT use this product outside of the specification range. Local regulations may restrict the use of this product to below the conditions quoted.

1 MPa = 10.197 kg/cm²

TLV.

Consulting · Engineering · Services

Configuration

No.	Description	Material	JIS	ASTM/AISI*
1	Main Body	Ductile Cast Iron	FCD450	A536
2	Cover	Ductile Cast Iron	FCD450	A536
3	Main Valve Seat	Stainless Steel	_	_
4	Main Valve	Stainless Steel	—	_
5	Main Valve Holder	Stainless Steel	—	_
6	Piston	Stainless Steel	—	_
7	Cylinder	Stainless Steel	—	_
8	Pilot Body	Ductile Cast Iron	FCD450	A536
9	Pilot Valve	Stainless Steel	—	_
(10)	Pilot Valve Seat	Stainless Steel	—	—
(1)	Diaphragm	Stainless Steel	—	—
(12)	Pilot Screen	Stainless Steel	—	—
(13)	Pilot Screen Holder	Carbon Steel	S25C	AISI1025
(14)	Diaphragm Support	Brass	—	—
(15)	Coil Spring	Carbon Steel	—	—
(16)	Spring Housing	Cast Iron	FC250	A126 Cl.B
(17)	Adjustment Screw	Cr-Mo Steel	—	—
(18)	Spanner Cap	Die Cast Aluminium	—	—
(19)	Plug – Sensing Line Port	Carbon Steel	SS400	A6
20	Pilot Cover	Ductile Cast Iron	FCD450	A536
21)	Nameplate	Stainless Steel	_	_
(22)	Plug – Blow Line Port	Carbon Steel	SS400	A6
23	Silencer	Stainless Steel	_	_





The parts configuration of sizes 65 to 100 mm differs slightly from that of sizes 15 to 50 mm.

* Equivalent

Contact TLV for available replacement parts. All gaskets are PTFE.

Cv Values

	Nominal Valve Size (mm)								
	15	20	25	32	40	50	65	80	100
Cv (US)	3.8	6.9	11.1	15.5	24.0	37.2	59.3	85.0	128
Cv (UK)	3.2	5.7	9.2	12.9	20.0	31.0	49.4	70.8	107
Kvs (DIN)	3.3	5.9	9.5	13.3	20.6	31.9	50.8	72.9	110

N The Cv & Kvs values shown are for the valve in the full fail open position. These values are not to be used for COSR sizing, and instead may be used as one of the factors in calculations for safety valve selection.

TLV.

Consulting · Engineering · Services

Sizing Chart



Dimensions



Size 15 to 50 mm shown. Configuration of larger sizes differs slightly.

Sizing Examples

For P1 over 1.6 MPaG

For primary pressure of 1.9 MPaG, set pressure 1.5 MPaG, and saturated steam flow rate 2800 kg/h, select an appropriate size.

- Locate intersecting point A₁ of 1.9 MPaG primary pressure and 1.5 MPaG set pressure. Go to point A₁ and down until 2800 kg/h, point B₁ is reached.
- 2. Since point B is located between 40 mm and 50 mm, the larger size, 50 mm, should be chosen.

Special Instructions for P1 under 1.6 MPaG

The vertical dotted lines in the graph represent the increased capacity often achievable when the internal sensing features of COSR-21 are enhanced by the installation of a $^{3}/_{8}$ inch external secondary pressure-sensing line (condition: $P_{2} < ^{1}/_{2} P_{1}$).



For primary pressure of 1.4 MPaG, set pressure 0.6 MPaG, and saturated steam flow rate 750 kg/h, select an appropriate size.

With internal secondary pressure-sensing channel

- 1. Locate intersecting point A of 1.4 MPaG primary pressure and 0.6 MPaG set pressure. Go to point A and down until 750 kg/h, point B, is reached.
- 2. Since point B is located between 20 mm and 25 mm, the larger size, 25 mm, should be chosen.

With external secondary pressure-sensing line

- 1. Obtain intersecting point C of 1.4 MPaG primary pressure. Go straight down from point C until 750 kg/h, point D, is reached.
- 2. Since point D is located between 15 mm and 20 mm, the larger size, 20 mm, should be chosen.

1 MPa = 10.197 kg/cm²

(mm)

COSR-21 Flanged

Size	ASME 150RF	L ASME Class 150RF 300RF		H1	W	Weight* (kg)	
(15)	161	167	405	405	205	105	11
(20)	172	178		305	105	13	
25	181	187	422	302	125	15	
32	212	219	457	322	150	19	
40	215	222	457			21	
50	254	260	490	335	195	36	
65	371	377	GEE	420	290	59	
80	374	384	055	430	200	62	
100	434	450	768	468	350	95	

() No ASME standard exists for ductile cast iron; machined to fit steel flanges Other standards available, but length and weight may vary * Weight is for Class 300 RF



Consulting · Engineering · Services

Option	
Pressure Gauge Unit	Replaces the standard screen holder plug to enable installation of a pressure gauge of the user's choice. Primary side: M16 holder plug (male/female), BSP/Rc(PT)/NPT ³ /8. An elbow is required for pressure gauge installation. Secondary side: Rc(PT) ³ /8 mounting port for elbow and pressure gauge installation.
	Elbows, pressure gauge and connecting parts must be purchased separately.

Configuration



• Installation Example



NOTE: For explanation purposes, a siphon tube style pressure gauge will be used. However, the instructions also apply to cooling tower-style pressure gauges.

No.	Part Name	No.	Part Name
1	Valve Body	5	Siphon Tube*
2	Holder Plug	6	Dampener*
3	Holder Plug Gasket	7	Dampener Gasket*
4	Elbow (male/female)*	8	Pressure Gauge*

* Purchase separately



Copyright © TLV

https://www.tlv.com

SDS M0000-70 Rev. 11/2024 Products for intended use only. Specifications subject to change without notice.

(T)